

1. Identification

Product identifier	Contec Bottles containing 70% Isopropyl alcohol, (7030LQFL)
Other means of identification	
SDS number	7030LQFL
Product code	HCCP7030FT-32, HCFT7030IR, HCFT7030IR-32, SB167030IR, SB327030, SB327030IR, SBT167030, SBT327030, SB327030IR-BR
Recommended use	Bottled IPA for critical cleaning.
Recommended restrictions	Uses other than the recommended use.
Manufacturer/Importer/Supplier/Distributor information	
Company name	Contec, Inc.
Address	525 Locust Grove Spartanburg, SC 29303 USA
Telephone	1-864-503-8333
Email	SDS@contecinc.com
Emergency phone number	Call CHEMTREC Day or Night USA/Canada: 1.800.424.9300 Mexico: 1.800.681.9531 Outside USA/Canada: +1.703.527.3887

2. Hazard identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity - single exposure	Category 3 narcotic effects

Label elements



Signal word	Danger
Hazard statement	Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statement	
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing mist/vapours. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell. In case of fire: Use appropriate media to extinguish.
Storage	Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Propan-2-ol		67-63-0	70
Water		7732-18-5	30

Composition comments

All concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause drowsiness or dizziness. Headache. Nausea, vomiting.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Take off all contaminated clothing immediately. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

May burn with invisible flame. Vapours may form explosive mixtures with air. Vapours are heavier than air and may spread near ground to sources of ignition. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Carbon oxides. Organic compounds.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Cool containers exposed to flames with water. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Highly flammable liquid and vapour.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Avoid contact with skin, eyes and clothing. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid release to the environment. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

WARNING! Used bottles may catch fire if improperly discarded or stored near ignition sources. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. Avoid breathing mist/vapours. Avoid contact with skin, eyes and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Keep away from combustible material. Keep containers closed when not in use. Keep in an area equipped with sprinklers. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. ACGIH Threshold Limit Values (TLV)**

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	STEL	984 mg/m ³
		400 ppm
	TWA	492 mg/m ³
		200 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191)

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	STEL	400 ppm

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191)

Components	Type	Value
	TWA	200 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	STEL	1230 mg/m3
		500 ppm
	TWA	985 mg/m3
		400 ppm

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	15 minute	400 ppm
	8 hour	200 ppm

Biological limit values

ACGIH Biological Exposure Indices (BEI)

Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Take note of the information given by the manufacturer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
Recommended materials: Polyethylene. Neoprene. Chlorinated polyethylene (or Chlorosulfonated polyethylene). Natural rubber. Polyvinyl chloride (PVC). Nitrile rubber/Nitrile latex - NBR.. Ethyl vinyl alcohol laminate ("EVAL").
Unsuitable materials: Polyvinyl alcohol (PVA).

Other

Wear suitable protective clothing.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapour cartridge and full facepiece. Check with respiratory protective equipment suppliers. Selection and use of respiratory protective equipment should be in accordance with CSA Standard Z94.4.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Physical state Liquid.

Form Liquid.

Colour	Colourless. Clear.
Odour	Alcoholic
Odour threshold	Property has not been measured.
Melting point/freezing point	Property has not been measured.
Boiling point or initial boiling point and boiling range	> 82 - < 89 °C (> 179.6 - < 192.2 °F)
Flammability	Highly flammable liquid and vapour.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	2 %
Explosive limit – upper (%)	12 %
Flash point	20.5 °C (68.9 °F)
Auto-ignition temperature	399 °C (750.2 °F)
Decomposition temperature	Property has not been measured.
pH	Property has not been measured.
Kinematic viscosity	Property has not been measured.
Solubility	
Solubility (water)	Completely Soluble (100%)
Partition coefficient (n-octanol/water) (log value)	Not applicable, the product is a mixture.
Vapour pressure	43 hPa (32 mm Hg) (20 °C (68 °F))
Density and/or relative density	
Density	Property has not been measured.
Relative density	0.872 (20 °C (68 °F))
Vapour density	Property has not been measured.
Particle characteristics	Not applicable (the material is a liquid).
Other information	
Evaporation rate	Property has not been measured.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
Percent volatile	100 % (IPA)
Viscosity	Property has not been measured.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. Protect against direct sunlight.
Incompatible materials	Aldehydes. Halogenated organics. Halogens. Strong acids. Strong oxidising agents.
Hazardous decomposition products	Combustion may produce: Oxides of carbon and other organic substances.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Prolonged skin contact may cause temporary irritation.
Eye contact	Causes serious eye irritation.

Ingestion	Ingestion may cause irritation and malaise.	
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause drowsiness or dizziness. Headache. Nausea, vomiting.	
Information on toxicological effects		
Acute toxicity	Not expected to be acutely toxic.	
Product	Species	Test Results
Contec Bottles containing 70% Isopropyl alcohol, (7030LQFL) (CAS Mixture)		
Acute		
Oral		
ATEmix		6729 mg/kg bw
Components	Species	Test Results
Propan-2-ol (CAS 67-63-0)		
Acute		
Dermal		
LD50	Rabbit	12870 mg/kg
Inhalation		
Vapour		
LC50	Rat	72.6 mg/l, 4 hours
Oral		
LD50	Rat	4710 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitisation		
Respiratory sensitisation	Not a respiratory sensitiser.	
Skin sensitisation	This product is not expected to cause skin sensitisation.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
ACGIH Carcinogens		
Propan-2-ol (CAS 67-63-0)	A4 Not classifiable as a human carcinogen.	
Canada - Manitoba OELs: carcinogenicity		
Propan-2-ol (CAS 67-63-0)	Not classifiable as a human carcinogen.	
Canada - New Brunswick OELs: Carcinogen category		
Propan-2-ol (CAS 67-63-0)	A4: Not classifiable as a human carcinogen	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Propan-2-ol (CAS 67-63-0)	3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Frequent or prolonged contact may defat and dry the skin.	

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
--------------------	--

Components	Species		Test Results
Propan-2-ol (CAS 67-63-0)			
Aquatic			
Acute			
Crustacea	LC50	Daphnia magna	> 10000 mg/l, 24 hours
Fish	LC50	Pimephales promelas	9640 mg/l, 96 hours
Chronic			
Crustacea	EC50	Daphnia magna	> 100 mg/l, 21 days
	NOEC	Daphnia magna	141 mg/l, 16 days
			30 mg/l, 21 days
Persistence and degradability	The product is readily biodegradable.		
Bioaccumulative potential	Bioconcentration potential is low.		
Partition coefficient n-octanol / water (log Kow)			
Propan-2-ol (CAS 67-63-0)	0.05		
Mobility in soil	Isopropyl alcohol is highly mobile in soil.		
Other adverse effects	The product contains a volatile organic compound which has a photochemical ozone creation potential.		

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

UN number	UN1219
UN proper shipping name	Isopropanol solution (Isopropanol), Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Packing group	II
Environmental hazards	No
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number	UN1219
UN proper shipping name	Isopropanol solution (Isopropanol), Limited Quantity
Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Packing group	II
Environmental hazards	No
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN1219
UN proper shipping name	Isopropanol solution (Isopropanol), Limited Quantity

Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Packing group	II
Environmental hazards	
Marine pollutant	No
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada Controlled Drugs and Substances Act, Schedule I

Not regulated.

Canada Controlled Drugs and Substances Act, Schedule II

Not regulated.

Canada Controlled Drugs and Substances Act, Schedule III

Not regulated.

Canada Controlled Drugs and Substances Act, Schedule IV

Not regulated.

Canada Controlled Drugs and Substances Act, Schedule V

Not regulated.

Canada Controlled Drugs and Substances Act, Schedule VI

Not regulated.

Canada Controlled Drugs and Substances Act, Schedule VII

Not regulated.

Canada Controlled Drugs and Substances Act, Schedule VIII

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not listed.

Rotterdam Convention

Not listed.

Kyoto Protocol

Not listed.

Montreal Protocol

Not listed.

Basel Convention

Not listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 02-September-2021

Revision date 15-October-2026

Version No. 04

Further information Further contact:
Maclsaac & Associates
440 Gloucester Street, Suite 2111
Ottawa, Ontario, K1R 7T8 Canada
+1 (613) 236-2250

Disclaimer Contec, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.